

Overview

The Pegasus Series is Amphenol Pcd's latest innovation in small, lightweight, rugged connectors. Designed for use in harsh environments, Pegasus builds on the successful Luminus Aerospace connector with the addition of EMI shielding.

EMI shielding is provided by electroless copper and nickel plate, with a copper alloy spring finger gasket to ensure shell-to-shell conductivity. Tests show between 40db and 60db of attenuation, depending on frequency. This combination of light weight, small size, and EMI shielding makes Pegasus the ideal choice where protection against ambient noise transients, or suppression of emitted noise is required, and space and weight are at a premium.

Features & Benefits

Electroless Copper & Nickel plating	Shielding from ambient noise transients, suppression of emitted noise (DO-160G Section 21 categories B, L and M and DO-160G Section 20 categories S & T)
1/4 turn bayonet style connection	Simple and easy mate & unmate; Blind mate keying
Interfacial and Triple-Barrier Seal	Environmental sealing to IP67
Multiple Configurations	Inline, Square Flange, Oval Flange, Jamnut PCB, Circular Snap-In
Scoop-Proof	Prevents contacts from being bent or electrically shorted during mating
Stainless Steel Contact Retainers	High contact retention force over operating life cycle

Materials & Specifications

Materials	Insulator Body: Ultem / Polyetherimide	Fluid Immersion	Lubricating Oil per Mil-Prf-7808
	Grommet & Face Seal: Silicone Rubber		Cleaning Compound per Mil-Prf-87937, Alkaline Base
	Contact Retainer: Stainless Steel		Isopropyl Alcohol & Mineral Spirit Solution
	Plating: Nickel over Copper		Skydrol Hydraulic Fluid
Temperature Range	-65°C to 125°C	Flammability	Hydraulic Fluids per MIL-PRF-83282 MIL-PRF-87257
Temperature Life	500 hours @ 85°C		Ethylene Glycol
Insulation Resistance	5000 MΩ Min. @ 500 VDC		Propylene Glycol
Dielectric Withstanding	1500 VAC, 60 Hz @ Sea Level, 1ma		Aviation Jet A
	300 VAC, 60 Hz @ 70,000 ft, 2ma	RoHS & REACH Compliance	UL94, V0.
Durability	Min 100 mating cycles; 250 typical		DOTG section 26.6.2 & 26.6.3
Temperature Cycling	5(1) Hour Cycles: -65°C to 125°C		FAR Part 25 App F Part I
Thermal Shock	-65°C to 200°C	Contact Insertion & Removal Force (not to exceed)	Yes
Vibration	30G Sinusoidal; 43.96G Random		less than 3 lbs
Shock	300G, 3msec, Half-Sine		less than 5 lbs insert (sz22)
Housing Electrical Conductivity	6 milliohm		less than 4lb remove (sz22)
EMI Shielding Effectiveness	65db @ 100Mhz 60db @ 200Mhz 55db @ 300Mhz 55db @ 400Mhz 45db @ 800Mhz 45db @ 1Ghz		less than 12lbs insert (sz 16)
			less than 12lbs remove (sz 16)
Salt Spray	5% Salt Spray @ 95°C for 48 Hours	Coupling Torque	greater than 10lbs
Humidity	10 Days @ 25°C to 65°C, 90% - 95% RH		less than 10lbs, sz 22
Seal Rating	IP67		less than 25lbs, sz 16
Altitude Immersion	Current Altitude Immersion Level Table Pgs. 2-3		less than 5lbs

Current Altitude Immersion Level by Part Number*

Part Number	Current Rating	PartNumber	Current Rating	Part Number	Current Rating	Part Number	Current Rating
SJS406120	50,000 ft	SJS862450	50,000 ft	SJS831100P	25,000 ft	SJS112460P	12,000 ft
SJS406120P	50,000 ft	SJS862450P	50,000 ft	SJS831101	25,000 ft	SJS112460P	12,000 ft
SJS406120-S	50,000 ft	SJS862451	50,000 ft	SJS831101P	25,000 ft	SJS112461	12,000 ft
SJS406121	50,000 ft	SJS862451P	50,000 ft	SJS812730	12,000 ft	SJS112461P	12,000 ft
SJS406121P	50,000 ft	SJS870510	50,000 ft	SJS812730P	12,000 ft	SJS112462	12,000 ft
SJS406121-S	50,000 ft	SJS870510P	50,000 ft	SJS812731	12,000 ft	SJS112462P	12,000 ft
SJS704120	50,000 ft	SJS870511	50,000 ft	SJS112120	12,000 ft	SJS112420P	12,000 ft
SJS704120P	50,000 ft	SJS870511P	50,000 ft	SJS112120P	12,000 ft	SJS112421	12,000 ft
SJS704121	50,000 ft	SJS861800	25,000 ft	SJS112121	12,000 ft	SJS812731P	12,000 ft
SJS704121P	50,000 ft	SJS861800P	25,000 ft	SJS112121P	12,000 ft	SJS112421P	12,000 ft
SJS809130	50,000 ft	SJS861801	25,000 ft	SJS112160	12,000 ft	SJS112460	12,000 ft
SJS809130P	50,000 ft	SJS861801P	25,000 ft	SJS112160P	12,000 ft	SJS861400	12,000 ft
SJS809131	50,000 ft	SJS831102	25,000 ft	SJS112161	12,000 ft	SJS861400M	12,000 ft
SJS809131P	50,000 ft	SJS831102P	25,000 ft	SJS112161P	12,000 ft	SJS861400P	12,000 ft
SJS830250	50,000 ft	SJS840410	25,000 ft	SJS112162	12,000 ft	SJS863460M	12,000 ft
SJS830250P	50,000 ft	SJS840410P	25,000 ft	SJS112162P	12,000 ft	SJS863461M	12,000 ft
SJS830250T	50,000 ft	SJS840411	25,000 ft	SJS112220	12,000 ft	SJS863600M	12,000 ft
SJS830251	50,000 ft	SJS840411P	25,000 ft	SJS112220P	12,000 ft	SJS863601M	12,000 ft
SJS830251P	50,000 ft	SJS840440	25,000 ft	SJS112221	12,000 ft	SJS863660M	12,000 ft
SJS840310	50,000 ft	SJS840440P	25,000 ft	SJS112221P	12,000 ft	SJS863661M	12,000 ft
SJS840310P	50,000 ft	SJS840441	25,000 ft	SJS112260	12,000 ft	SJS112261	12,000 ft
SJS840311	50,000 ft	SJS840441P	25,000 ft	SJS112260P	12,000 ft	SJS112261P	12,000 ft
SJS840311P	50,000 ft	SJS706160	25,000 ft	SJS861401	12,000 ft	SJS112262	12,000 ft
SJS840340	50,000 ft	SJS706160P	25,000 ft	SJS861401M	12,000 ft	SJS112262P	12,000 ft
SJS840340P	50,000 ft	SJS706161	25,000 ft	SJS861401P	12,000 ft	SJS112320	12,000 ft
SJS840341	50,000 ft	SJS706161P	25,000 ft	SJS861460M	12,000 ft	SJS112320P	12,000 ft
SJS840341P	50,000 ft	SJS706162	25,000 ft	SJS861461M	12,000 ft	SJS112321	12,000 ft
SJS862200	50,000 ft	SJS706162P	25,000 ft	SJS863200M	12,000 ft	SJS112321P	12,000 ft
SJS862200P	50,000 ft	SJS830100	25,000 ft	SJS863201M	12,000 ft	SJS112360	12,000 ft
SJS862201	50,000 ft	SJS830100P	25,000 ft	SJS863260M	12,000 ft	SJS112360P	12,000 ft
SJS862201P	50,000 ft	SJS830101	25,000 ft	SJS863261M	12,000 ft	SJS112361	12,000 ft
SJS862400	50,000 ft	SJS830101P	25,000 ft	SJS863400M	12,000 ft	SJS112361P	12,000 ft
SJS862400P	50,000 ft	SJS830102	25,000 ft	SJS863401M	12,000 ft	SJS112362	12,000 ft
SJS862401	50,000 ft	SJS830102P	25,000 ft	SJS112362P	12,000 ft		
SJS862401P	50,000 ft	SJS831100	25,000 ft	SJS112420	12,000 ft		

*Luminus - SJS and Pegasus SJSxP

Current Altitude Immersion Level by Part Number*

Part Number	Current Rating	PartNumber	Current Rating	Part Number	Current Rating
SJS0AA730	IP67, Sea Level	SJS225120M	IP67, Sea Level	SJS425120	IP67, Sea Level
SJS0AA730P	IP67, Sea Level	SJS225121M	IP67, Sea Level	SJS425120P	IP67, Sea Level
SJS0AA731	IP67, Sea Level	SJS225160M	IP67, Sea Level	SJS425121	IP67, Sea Level
SJS0AA731P	IP67, Sea Level	SJS225161M	IP67, Sea Level	SJS425121P	IP67, Sea Level
SJS0AA737P	IP67, Sea Level	SJS225162M	IP67, Sea Level	SJS425160	IP67, Sea Level
SJS0AB770	IP67, Sea Level	SJS225220M	IP67, Sea Level	SJS425160P	IP67, Sea Level
SJS0AB770P	IP67, Sea Level	SJS225221M	IP67, Sea Level	SJS425161	IP67, Sea Level
SJS0AB771	IP67, Sea Level	SJS225260M	IP67, Sea Level	SJS425161P	IP67, Sea Level
SJS0AB771P	IP67, Sea Level	SJS225261M	IP67, Sea Level	SJS425162	IP67, Sea Level
SJS860200	IP67, Sea Level	SJS225262M	IP67, Sea Level	SJS425162P	IP67, Sea Level
SJS860200P	IP67, Sea Level	SJS225320M	IP67, Sea Level	SJS425220	IP67, Sea Level
SJS860201	IP67, Sea Level	SJS225321M	IP67, Sea Level	SJS425220P	IP67, Sea Level
SJS860201P	IP67, Sea Level	SJS225360M	IP67, Sea Level	SJS425221	IP67, Sea Level
SJS860500	IP67, Sea Level	SJS225361M	IP67, Sea Level	SJS425221P	IP67, Sea Level
SJS860500P	IP67, Sea Level	SJS225362M	IP67, Sea Level	SJS425260	IP67, Sea Level
SJS860501	IP67, Sea Level	SJS225420M	IP67, Sea Level	SJS425260P	IP67, Sea Level
SJS860501P	IP67, Sea Level	SJS225421M	IP67, Sea Level	SJS425261	IP67, Sea Level
SJS860520	IP67, Sea Level	SJS225460M	IP67, Sea Level	SJS425261P	IP67, Sea Level
SJS860520P	IP67, Sea Level	SJS225461M	IP67, Sea Level	SJS425262	IP67, Sea Level
SJS860521	IP67, Sea Level	SJS225462M	IP67, Sea Level	SJS425262P	IP67, Sea Level
SJS860521P	IP67, Sea Level	SJS412120	IP67, Sea Level	SJS425320	IP67, Sea Level
SJS860900	IP67, Sea Level	SJS412120P	IP67, Sea Level	SJS425320P	IP67, Sea Level
SJS860900P	IP67, Sea Level	SJS412121	IP67, Sea Level	SJS425321	IP67, Sea Level
SJS860901	IP67, Sea Level	SJS412121P	IP67, Sea Level	SJS425321P	IP67, Sea Level
SJS860901P	IP67, Sea Level	SJS805730	IP67, Sea Level	SJS425360	IP67, Sea Level
SJS861200	IP67, Sea Level	SJS805730P	IP67, Sea Level	SJS425360P	IP67, Sea Level
SJS861200P	IP67, Sea Level	SJS805731	IP67, Sea Level	SJS425361	IP67, Sea Level
SJS861201	IP67, Sea Level	SJS805731P	IP67, Sea Level	SJS425361P	IP67, Sea Level
SJS861201P	IP67, Sea Level	SJS830210	IP67, Sea Level	SJS425362	IP67, Sea Level
SJS8AC730	IP67, Sea Level	SJS830210P	IP67, Sea Level	SJS425362P	IP67, Sea Level
SJS8AC730P	IP67, Sea Level	SJS830211	IP67, Sea Level	SJS425420	IP67, Sea Level
SJS8AC731	IP67, Sea Level	SJS830211P	IP67, Sea Level	SJS425420P	IP67, Sea Level
SJS8AC731P	IP67, Sea Level	SJS425421	IP67, Sea Level	SJS425460	IP67, Sea Level
SJS425461	IP67, Sea Level	SJS425421P	IP67, Sea Level	SJS425460P	IP67, Sea Level
SJS425461P	IP67, Sea Level	SJS425462	IP67, Sea Level	SJS425462P	IP67, Sea Level

*Luminus - SJS and Pegasus SJSxP

Part Numbering: Twist & Lock

											
# of Positions	Contact Size	Shell Size	Key	Color	Plug	Inline	Circular	Square	Jamnut	Oval	Jamnut Rear Mount
1	Quadrax	8	-	-	SJS801110P	SJS801120P	-	SJS801130P*	SJS801160P*	SJS801170P*	SJS801190P*
2	22D	5	-	Black	SJS830250P	SJS830270P	-	-	SJS502160P	SJS502170P	SJS502190P
3	12	10	-	-	SJS003110P*	SJS003120P*	-	-	-	-	-
3	16	8	A	White	SJS840310P	SJS840300P	SJS840320P	SJS803730P*	-	-	-
3	16	8	B	Black	SJS840340P	SJS840350P	SJS840330P	SJS803130P*	-	-	-
3	20	7	-	White	SJS862300P	SJS862400P	-	SJS862450P	-	-	-
3	22D	5	-	Black	SJS830210P	SJS830230P	-	-	SJS503160P	SJS503170P	SJS503190P
4	16	8	A	White	SJS840410P	SJS840400P	SJS840420P	SJS840740P	SJS840760P*	-	SJS840790P*
4	16	8	B	Green	SJS840440P	SJS840450P	SJS840430P*	-	-	-	-
4	20	7	-	Black	SJS704110P	SJS704120P	SJS704130P*	-	-	-	-
5	22D	8	-	White	SJS860510P	SJS860500P	SJS860520P	SJS805730P	-	-	-
5	22D	8	-	White	SJS870510P	SJS860510P	SJS870520P	-	-	-	-
6	22D	7	-	Black	SJS861700P	SJS861800P	-	-	SJS706160P	-	-
8	22D	7	A	Black	SJS830100P	SJS830200P	-	SJS830220P	SJS708160P	SJS708170P	SJS708190P
8	22D	7	B	Green	SJS830101P	SJS830201P	-	SJS830221P	-	-	-
8	22D	7	C	Yellow	SJS830102P	SJS830202P	-	SJS830222P	-	-	-
9	22D	8	-	Black	SJS862100P	SJS862200P	-	SJS809130P*	-	-	-
12	16	14	-	Black	SJS412110P*	SJS412120P*	-	-	-	-	-
12	22D	8	-	White	SJS861300P	SJS861400P	-	SJS812730P	SJS812760P*	-	-
12	22D	11	A	Black	SJS112110P	SJS112120P	-	-	SJS112160P	-	-
12	22D	11	B	Green	SJS112210P	SJS112220P	-	-	SJS112260P	-	-
12	22D	11	C	White	SJS112310P	SJS112320P	-	-	SJS112360P	-	-
12	22D	11	D	Yellow	SJS112410P	SJS112420P	-	-	SJS112460P	-	-
25	22D	14	A	Black	SJS425110P	SJS425120P	-	-	SJS425160P	-	-
25	22D	14	B	Green	SJS425210P	SJS425220P	-	-	SJS425260P	-	-
25	22D	14	C	White	SJS425310P	SJS425320P	-	-	SJS425360P	-	-
25	22D	14	D	Yellow	SJS425410P	SJS425420P	-	-	SJS425460P	-	-
5	12 (3)	11	-	Black	SJS1AE110P*	SJS1AE120P*	-	-	-	-	-
	22 (2)										
9	16 (1)	8	-	White	SJS860100P	SJS860200P	-	-	-	-	-
	22D (8)										
9	16 (4)	10	-	White	SJS860910P	SJS860900P	-	SJS0AA730P	-	-	-
	22D (5)										
10	16 (4)	10	-	White	SJS861100P	SJS861200P	SJS0AB730P*	-	-	SJS0AB770P	-
	22D (6)										

* Available at extended lead times