

SOLDIER WORN CABLES

Overview

New from Amphenol PCD, off the shelf solutions on common charging interfaces used for the Nett Warrior. Offering a diverse selection of charging capabilities that gives the opportunity to choose from USB2.0 Type A, Type C, Micro-B, and a pigtail to attach any interface that meets customer needs. In need of charging capabilities for the Nett Warrior project? Amphenol PCD has the solution for you.

MCNW-000-M6S-XXX



Nett warrior Pigtail ASSY,
Male, 6-POS

MCNW-000-F6S-XXX



Nett Warrior Pigtail ASSY,
Female, 6-POS

MCNW-001-FM6S-XXX



Nett Warrior to Nett Warrior
Receptacle-to-Plug Cordset

MCNW-002-MM6S-XXX



Nett Warrior Plug to
USB2.0 Type-A Plug

MCNW-003-MM6S-XXX



Nett Warrior Receptacle to
USB2.0 Micro-B Plug

MCNW-004-FM6S-XXX



Nett Warrior Plug to
USB2.0 Type-C Plug

SOLDIER WORN CABLES

How to Order

MCNW - 003 - FM6S-036

Cable Series _____

- 000: Nett warrior Pigtail ASSY
- 001: Nett Warrior to Nett Warrior Receptacle-to-Plug Cordset
- 002: Nett Warrior Plug to USB2.0 Type-A Plug
- 003: Nett Warrior Receptacle to USB2.0 Micro-B Plug
- 004: Nett Warrior Plug to USB2.0 Type-C Plug

P1 Gender _____

- M: Nett Warrior plug w/ pins
- F: Nett Warrior receptacle w/ sockets

P2 Gender _____

- M: USB Micro B plug w/ 5 contacts

P1 Number of Contacts _____

- 6: 6-6 Arrangement
- 7: 6-7 Arrangement

P2 Amperage Rating _____

- S: 5 A (Standard)
- A: 10 A (Extended)

Length: Inches _____

- Standard cable lengths (Adapter Cables): 8 in, 10 in, 12 in
- Standard cable lengths (Pigtails): 6 in, 12 in, 18 in
- Custom cable lengths are available
- Wiring, labels, & molding markings can be customized upon request
- Meets IPC-WHMA-A-620B
- Quick turnaround times
- XXX = Length in inches (012 = 12 inches)

Order by Email

Email your engineered drawing and parts list to you local Amphenol Sales Representative or info@amphenolpcd.com

Order by Phone

Call Amphenol Pcd with your cable needs at: 978-624-3400 or 941-773-8560

